

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 - United Kingdom (UK)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : Hempel's Classic 71220  
Product identity : 7122019990, 00134543  
Product type : antifouling paint

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : yacht, ships and shipyards.  
Identified uses : Consumer applications, Professional applications, Used by spraying.  
Spraying - For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel UK Ltd  
Berwyn House, The Pavilions  
Llantarnam Park  
Cwmbran  
South Wales NP44 3FD  
Telephone: 01633 833600  
hempel@hempel.com

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)

UK: **01633 833600** (08.00 - 17.00)  
Ireland: **01 809 2166** (National Poisons Information Centre,  
Monday-Sunday; 08:00-22:00)

See Section 4 of the safety data sheet (first aid measures).

Date of issue : 27 August 2025  
Date of previous issue : 10 July 2025.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

##### Classification according to UK CLP/GHS

Flam. Liq. 3, H226	FLAMMABLE LIQUIDS
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/EYE IRRITATION
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation)
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects)
Aquatic Acute 1, H400	SHORT-TERM (ACUTE) AQUATIC HAZARD
Aquatic Chronic 1, H410	LONG-TERM (CHRONIC) AQUATIC HAZARD

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :  
H226 - Flammable liquid and vapour.  
H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention : Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapour.  
Response : Collect spillage. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.  
Storage : Store locked up. Store in a well-ventilated place. Keep container tightly closed.

### SECTION 2: Hazards identification

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Solvent naphtha (petroleum), light arom.  
copper (I) oxide

Supplemental label elements : Repeated exposure may cause skin dryness or cracking.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Product/ingredient name	Identifiers	%	GB CLP Classification	Type
Solvent naphtha (petroleum), light arom.	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 64742-95-6	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≥10 - ≤25	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
copper (I) oxide	REACH #: 01-2119513794-36 EC: 215-270-7 CAS: 1317-39-1 Index: 029-002-00-X	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
copper oxide	EC: 215-269-1 CAS: 1317-38-0 Index: 029-016-00-6	≤1	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=1)	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

#### Active substances

Product/ingredient name (% by weight)
copper (I) oxide (10.1 % by weight)

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

### SECTION 4: First aid measures

Inhalation :	Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.
Protection of first-aiders :	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact :	Causes serious eye damage.
Inhalation :	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact :	Defatting to the skin. May cause skin dryness and irritation.
Ingestion :	Can cause central nervous system (CNS) depression.

#### Over-exposure signs/symptoms

Eye contact :	Adverse symptoms may include the following: pain watering redness
Inhalation :	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact :	Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Ingestion :	Adverse symptoms may include the following: stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray. Not to be used : waterjet.
-----------------------	------------------------------------------------------------------------------------------------------------

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides metal oxide/oxides

## SECTION 5: Firefighting measures

### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

Specific end use(s) : Antifouling products.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers]</b> Absorbed through skin. STEL 15 minutes: 441 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm.

##### Biological exposure indices

Product/ingredient name	Exposure limit values
xylene	<b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers]</b> BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

##### Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

##### Derived effect levels

Not applicable.

##### Predicted effect concentrations

Not applicable.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection :

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

### SECTION 8: Exposure controls/personal protection

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®

May be used: nitrile rubber (>0.3 mm)

Short term exposure: neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

**Body protection :** Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.  
Wear suitable protective clothing. Always wear protective clothing when spraying.  
Chemical-resistant apron.

**Respiratory protection :** When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

**Physical state :** Liquid.

**Colour :** Black.

**Odour :** Solvent-like

**pH :** Testing not relevant or not possible due to nature of the product.

**Melting point/freezing point :** Testing not relevant or not possible due to nature of the product.

**Boiling point/boiling range :** Testing not relevant or not possible due to nature of the product.

**Flash point :** Closed cup: 37°C (98.6°F)

**Evaporation rate :** Testing not relevant or not possible due to nature of the product.

**Flammability :** Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Vapour pressure :		Vapour Pressure at 20°C			Vapour pressure at 50°C		
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
	Solvent naphtha (petroleum), light arom.	0.8 - 4.6	0.11 - 0.61				

**Vapour density :** Not available.

**Specific gravity :** 1.44 g/cm<sup>3</sup>

**Partition coefficient (LogKow) :** Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature :	Ingredient name	°C	°F	Method
	Solvent naphtha (petroleum), light arom.	280 - 470	536 - 878	

**Decomposition temperature :** Testing not relevant or not possible due to nature of the product.

**Viscosity :** Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.

**Explosive properties :** Testing not relevant or not possible due to nature of the product.

**Oxidising properties :** Testing not relevant or not possible due to nature of the product.

#### 9.2 Other information

**Solvent(s) % by weight :** Weighted average: 30 %

**Water % by weight :** Weighted average: 0 %

**VOC content :** 424.2 g/l

### SECTION 9: Physical and chemical properties

TOC Content : Weighted average: 381 g/l  
Solvent Gas : Weighted average: 0.091 m³/l

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.  
Slightly reactive or incompatible with the following materials: reducing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Direct contact with the eyes can cause irreversible damage, including blindness.

#### Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
7122019990	Rat - Oral - LD50	>2000 mg/kg	
Solvent naphtha (petroleum), light arom.	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Oral - LD50	3492 mg/kg	
zinc oxide	Rabbit - Dermal - LD50	3160 mg/kg	
	Rat - Inhalation - LC50 Vapour	6193 mg/m³ [4 hours]	
	Rat - Oral - LD50	>5000 mg/kg	
	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	>5.7 mg/l [4 hours]	
copper (I) oxide	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Oral - LD50	1340 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	3.34 mg/l [4 hours]	
xylene	Rabbit - Dermal - LD50	>4200 mg/kg	
	Rat - Oral - LD50	3523 mg/kg	
	Rat - Inhalation - LC50 Vapour	6350 ppm [4 hours]	
	Rat - Inhalation - LC50 Gas.	5000 ppm [4 hours]	

#### Acute toxicity estimates



### SECTION 11: Toxicological information

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapours) mg/l	Inhalation (dusts and mists) mg/l
Hempel's Classic 71220					
Solvent naphtha (petroleum), light arom.	3492	3160	170711.5		33.2
copper (I) oxide	500				3.34
xylene	3523	1100	5000		

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 microliters
zinc oxide	Rabbit - Respiratory - Mild irritant Rabbit - Skin - Moderate irritant Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams
copper (I) oxide	Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 milligrams
xylene	Rabbit - Eyes - Irritant Rabbit - Eyes - Severe irritant Rabbit - Skin - Moderate irritant Rabbit - Skin - Irritant	Duration of treatment/ exposure: 24 hours Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 5 milligrams Amount/concentration applied: 500 milligrams

#### Sensitiser

No known data available in our database.

#### Mutagenic effects

No known data available in our database.

#### Carcinogenicity

No known data available in our database.

#### Reproductive toxicity

No known data available in our database.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), light arom.	Category 3 Category 3		Respiratory tract irritation Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
No known data available in our database.			

#### Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

#### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

No known significant effects or critical hazards.

#### 11.2 Information on other hazards

Other information : No additional known significant effects or critical hazards.



### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Very toxic to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), light arom.	Acute - LC50	Fish - <i>Oncorhynchus mykiss</i> (rainbow trout)	9.22 mg/l [96 hours]
zinc oxide	Acute - EC50	Algae - <i>Pseudokirchneriella subcapitata</i> (green algae)	2.6 mg/l [96 hours]
	Acute - EC50	Daphnia	3.2 mg/l [48 hours]
	Acute - LC50 - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	24600 µg/l [48 hours]
	Acute - EC50	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i> - Exponential growth phase	0.17 mg/l [72 hours]
	Acute - EC50	Daphnia - Green algae - <i>Pseudokirchneriella subcapitata</i> - Exponential growth phase	1 mg/l [48 hours]
copper (I) oxide	EC50	Daphnia	0.413 mg/l [48 hours]
	LC50	Fish	0.1169 mg/l [96 hours]
	Chronic - EC50	Algae	0.136 mg/l [72 hours]
	Acute - EC50	Algae	65 mg/l [96 hours]
	Acute - LC50	Fish - <i>Pimephales promelas</i>	0.0081 mg/l [96 hours]
	Acute - EC50	Daphnia - <i>Daphnia magna</i>	0.51 mg/l [48 hours]

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result
Solvent naphtha (petroleum), light arom.		>70% [28 days] - Readily
xylene	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 78% [28 days] - Readily
	OECD Ready Biodegradability - Manometric Respirometry Test	>60% [28 days] - Readily 90 - 98% [28 days] - Readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Solvent naphtha (petroleum), light arom.			Readily
zinc oxide			Not readily
xylene			Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Solvent naphtha (petroleum), light arom.	-	10 - 2500	High
zinc oxide	2.2	60960	High
xylene	3.12	8.1 - 25.9	Low

#### 12.4 Mobility in soil

##### Soil/water partition coefficient

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
xylene	1.59	39

##### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Solvent naphtha (petroleum), light arom.	No	No	No	No	No	No	No
zinc oxide	No	No	No	No	No	No	No
copper (I) oxide	No	No	No	No	No	No	No
xylene	No	No	Yes	No	No	No	Yes
copper oxide	No	No	No	No	No	No	No

Mobility : The product does not meet the criteria to be considered as a PMT or vPvM.

#### 12.5 Results of PBT and vPvB assessment

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.

### SECTION 12: Ecological information

#### 12.6 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.






European waste catalogue (EWC) : 08 01 11\*

#### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
<b>ADR/RID Class</b>	UN1263	PAINT	3  	III	Yes.	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Tunnel code</b> (D/E)
<b>IMDG Class</b>	UN1263	PAINT. (Solvent naphtha (petroleum), light arom.)	3  	III	Yes.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <b>Emergency schedules</b> F-E, S-E
<b>IATA Class</b>	UN1263	PAINT	3 	III	Yes.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation - Substances of very high concern

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

##### Other EU regulations

### SECTION 15: Regulatory information

**Seveso category** This product is controlled under the Seveso III Directive.

#### Seveso category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b  
E1: Hazardous to the aquatic environment - Acute 1 or Chronic 1

#### Biocidal Products Regulations

Restrictions on use : See Section 1: Relevant identified uses of the substance or mixture and uses advised against

Directions for use and dose rate : Spray or Roller application or brushing  
Consumer use: Rolling, Brushing  
Dose: See separate Product Data Sheet, Application instructions or label.

Additional information : (Product Type: 21 - Antifouling products) Liquid. Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes, rinse immediately with plenty of water. If swallowed, seek medical advice immediately and show the container or label. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Refer to special instructions/safety data sheet.

#### International regulations

##### IMO Anti-fouling System Convention Compliant (AFS/CONF/26)

This product does not contain organotin compounds acting as biocides and complies with the International Convention on the Control of Harmful Anti-fouling Systems on Ships as adopted by IMO October 2001 (IMO document AFS/CONF/26)

Product type : antifouling paint  
Manufacturer : Hempel A/S  
Product name and/or code : Hempel's Classic 71220

7122019990

Colour : Black.

Note: This name is shown on the product container. All products in HEMPEL's containers carrying this name comply with the IMO Convention (AFS/CONF/26).

Active ingredient(s) : copper (I) oxide 1317-39-1

#### 15.2 Chemical safety assessment

Not applicable.

### SECTION 16: Other information

Abbreviations and acronyms : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
EUH statement = CLP-specific Hazard statement  
RRN = REACH Registration Number  
DNEL = Derived No Effect Level  
PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements : H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS] : Acute Tox. 4 ACUTE TOXICITY - Category 4  
Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1  
Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1  
Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  
Asp. Tox. 1 ASPIRATION HAZARD - Category 1  
Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### SECTION 16: Other information

Classification	Justification
FLAMMABLE LIQUIDS	On basis of test data
SERIOUS EYE DAMAGE/EYE IRRITATION	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation)	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects)	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD	Calculation method

#### Notice to reader

▣ Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.